

Precision Measuring Instruments





Vibration Tester PV-400



PV400 uses piezoelectric acceleration transducer to convert vibration signal into electric signal. Then by analyzing input signal, results including RMS of velocity values, peak-peak value of displacement, peak values of acceleration or real-time spectral charts are displayed or printed out. It can not only measure the three parameters, but also for rotational speed measuring.

The vibration meter is designed to test conventional vibration, especially the vibration test in rotating and reciprocating machines. It can be used not only to test the acceleration, velocity, and displacement of vibration as well as rev (or inherent frequency), but also perform simple failure diagnosis.

The technical specifications of PV400 comply with the requirements of GB 13823.3. PV400 is widely used in machinery, power, metallurgy, automobile and other industrial fields.

Technical specifications

Testing range (Metric) Testing range (Imperial)	Acce: 0.1 ~ 205.6 m/s ² (peak) Velo: 0.1 ~ 400.0 mm/s(RMS) Disp: 0.001 ~ 9.0 mm(peak-peak) Acce: 0.01 ~ 20.98 g(peak) Velo: 0.01 ~ 15.75 in/s(RMS) Disp: 0.1 ~ 354.3 mil(peak-peak)			
Freq range	Acceleration: 10Hz ~ 200Hz, 10Hz ~ 500Hz, 10Hz ~ 1KHz, 10Hz ~ 10KHz Velocity: 10Hz ~ 1KHz Displacement: 10Hz ~ 500Hz			
Frequency resolution	0.25Hz			
Data memory	100 × 80 pieces of data and 100 spectrums			
Software	Yes			
Temp	0°C~ 40°C			
Tolerance	±5%			
Speed measuring range	30 ~ 300000 rpm corresponding to 0.5 ~ 5000Hz			
Measuring distance	0.15 ~ 1m			
Display	TFT 320×200 pixels with RGB			
Data interface	USB			
Overall dimensions	212×80×35			

Printer	Integrated thermal printer
Weight	320g
Battery	Rechargeable Li battery,1500mAh
Continuous working time	About 50h

Configuration

	NO.	Item	Quantity
	1	Main uni.	1
	1	Power Adapters (input:220V/50Hz, output:9V/1000mA)	1
Standard			
configuration	3	Piezoelectric sensors	1
	4	Magnetic seat (with 2 bolts)	1
	5	Manual	1
	6	Communication cable	1
	7	Package case	1
Optional configuration	1	Speed transducer (Lacer)	1
	2	Software	1
	3	Probe	1