

Postbus 540 7550 AM Hengelo (Ov) +31(0)74 3490022 www.naumetrics.nl info@naumetrics.nl



## **NR145 Precision Colorimeter**



NR145 is a precision colorimeter with  $45^{\circ}/0^{\circ}$  viewing angle after NH310, NH300, NR200, NR110 and NR100 colorimeter. NR145 colorimeter has strong functions which applied a number of differential innovative technologies. It can measure accurately in  $45^{\circ}$  illumination  $/0^{\circ}$  receiving under the SCE mode.



Postbus 540 7550 AM Hengelo (Ov) +31(0)74 3490022 www.naumetrics.nl info@naumetrics.nl



## **Product Advantages**

- 1. Built-in white plate parameters. No need to calibrate each time which can perform measurement quickly.
- 2. Double Locating: Illuminating locating and precise cross locating.
- 3. Switchable Double Measurement End Face: Large stable end face and small concave-convex end face.
- 4. New 45°/0° Optical Path Design: Significantly improve the measurement stability and precision.
- 5.8mm Measuring Aperture.
- 6. Equipped with rechargeable high-capacity Li-ion battery. No need to purchase battery repeatedly.
- 7. Configure CQCS3 software. Connect PC computer to realize more functions.
- 8. Having got SCM Metrological Certification, CE Certification, and ISO9001 Quality Management System Certification.
- 9. Hand-head structure: small and convenient; make the measurement easier.
- 10. Exquisite appearance: adopts traditional and fashionable aesthetic designs.











Postbus 540 7550 AM Hengelo (Ov) +31(0)74 3490022 www.naumetrics.nl info@naumetrics.nl



	NR145
Illuminating/Viewing Geometry	45°/0°
Measuring Aperture	Φ8mm
Measurement End-face	Large stable end face and small concave-convex end face
Detector	Silicon photoelectric diode
Locating	Illuminating Locating/Cross Locating
Color Space	CIEL*a*b*C*h* CIEL*a*b* CIEXYZ
Color Difference Formula	ΔE*ab ΔL*a*b* ΔE*C*h*
Light Source	D65
Light Source Device	LED blue light excitation
Errors Between Each Equipment	≤0.80∆E*ab
Storage	100pcs standards 20000pcs samples
Repeatability	Standard deviation within $\Delta E^*ab 0.08$ Average of 30 measurements of standard white plate
Weight	500g
Dimension	205×67×80 mm
Power source	Rechargeable lithium-ion battery 3.7V@3200mAh
Lamp Life	5 years, more than 1.6 million measurements
Charging Time	The charging time is 8 hours100% electricity
PC Software	CQCS3 Software
Printer (optional)	Miniature thermal printer